Serial No. 10/783,668

Attorney Docket No. IS01442ESG

## **CLAIMS:**

18475232350

- (Original) A machine for removing debris from battery cells, comprising:
  - a. a means for holding a battery cell; and
  - b. a cutting means comprising at least one blade;

wherein when a battery cell is inserted into the means for holding a battery cell, and the cutting means is actuated, the at least one blade passes across at least one surface of the battery cell.

- (Original) The machine of claim 1, wherein the cutting means further comprises a leveling means.
- 3. (Original) The machine of claim 2, wherein when a battery cell is inserted into the means for holding a battery cell, the amount of insertion is limited by the leveling means.
- 4. (Original) The machine of claim 1, further comprising a magnet mounted below the cutting means.
- 5. (Original) The machine of claim 1, wherein the means for holding a battery cell comprises a fixed block and a moveable belt.
- 6. (Original) The machine of claim 5, wherein the moveable belt is spring loaded against the fixed block.
- 7. (Currently Amended) The machine of claim [[1]] 3, further comprising a sliding member coupled to the cutting means, wherein the sliding member is mounted on rails.
- 8. (Original) The machine of claim 7, wherein the sliding member is coupled to a lever.
- 9. (Original) The machine of claim 8, wherein lever is rotatably connected to the sliding member by way of a gear assembly.
- 10. (Original) The machine of claim 7, further comprising a threaded member coupled to the sliding member, wherein the threaded member passes through a fixed adjustment stop.
- 11. (Original) The machine of claim 10, further comprising a threaded stop disposed about the threaded member such that the fixed adjustment stop is disposed between the sliding member and the threaded stop.

Scrial No. 10/783,668

Attorney Docket No. 1SQ1442ESG

- (Original) The machine of claim 11, wherein travel of the cutting means is adjustable by 12. twisting the threaded stop about the threaded member.
- 13. (Original) The machine of claim 1, wherein the cutting means is electrically isolated from the means for holding a battery cell.
- (Withdrawn) A method of removing debris from a battery cell, the method comprising the steps of: 14.

18475232350

- providing the machine of claim 1; a.
- opening the means for holding a battery cell; b.
- inserting a battery cell into the means of holding a battery cell until one end of the battery c. cell touches the leveling means;
  - d. closing the means for holding a battery cell; and
- actuating the cutting means, thereby causing the cutting means to pass along the one end of e. the battery cell.
- 15. (Currently Amended) A machine for removing debris from a battery cell, comprising;
  - a base member; a.
- Ь. a fixed block coupled to the base member, wherein the fixed block includes a recess for holding the battery cell;
- a moveable belt that is spring loaded against the fixed block such that the recess and the moveable belt form a closed loop; and
  - a moveable cutting means comprising at least one blade; d.

wherein when the moveable cutting means is moving, the at least one blade travels parallel to the top surface of the leveling cutting means.

- (Original) The machine of claim 15, wherein the moveable cutting means further comprises a leveling means.
- 17. (Original) The machine of claim 15, further comprising a magnet disposed below the cutting means.
- (Original) The machine of claim 15, wherein the cutting means is electrically isolated from the 18. fixed block and the moveable belt.